

MICHIGAN
DEPARTMENT OF TRANSPORTATION

SPECIAL PROVISION
FOR
DRAINAGE MARKER POSTS

RSD:NJM

1 of 1

APPR:MKB:DMG:06-16-25
FHWA:APPR:06-17-25

Delete subsection 401.03.F, on page 4-8 of the Standard Specifications for Construction, in its entirety and replace it with the following:

- F. **Drainage Marker Posts.** Place drainage marker posts at headwalls and culvert end sections for culverts with a diameter no greater than 36 inches and at outlet endings. Install drainage marker posts at least 2 feet deep or as recommended by the manufacturer.

Attach green aluminum reflectors meeting the requirements as specified in subsection 919.03 for delineators.

Delete subsection 401.04.I, on page 4-13 of the Standard Specifications for Construction, in its entirety and replace it with the following:

- I. The unit price for **Dr Marker Post** includes the cost of providing and installing the post as described in subsection 401.03.F. Reflectors are paid for separately as **Delineator Reflector, Green** according to subsection 810.04.

Delete section 909.10, on page 9-72 of the Standard Specifications for Construction, in its entirety and replace it with the following:

909.10. Drainage Marker Posts

Provide drainage marker posts meeting the requirements for rigid steel delineator posts as specified in section 919.03, except provide posts at least 6 feet long.