

MICHIGAN
DEPARTMENT OF TRANSPORTATION

SPECIAL PROVISION
FOR
DRAINAGE MARKER POSTS

RSD:NJM

1 of 1

APPR:MKB:DMG:11-21-25
FHWA:APPR:11-21-25

Delete subsection 401.03.F, on page 4-8 of the Standard Specifications for Construction, in its entirety and replace it with the following:

- F. **Drainage Marker Posts.** Place drainage marker posts at all underdrain outlets, culvert end treatments no greater than 36 inches, and drainage structures outside the paved area. Install drainage marker posts at least 2 feet deep or as recommended by the manufacturer.

Mount green reflectors facing towards the road such that they are not reflecting upon drivers on the travelled way. Reflectors and mounting hardware must be in accordance with subsection 919.03 for delineators.

Delete subsection 401.04.I, on page 4-13 of the Standard Specifications for Construction, in its entirety and replace it with the following:

- I. The unit price for **Dr Marker Post** includes the cost of providing and installing the post as described in subsection 401.03.F. Reflectors are paid for separately as **Delineator Reflector, Green** according to subsection 810.04.

Delete section 909.10, on page 9-72 of the Standard Specifications for Construction, in its entirety and replace it with the following:

909.10. Drainage Marker Posts

Provide drainage marker posts meeting the requirements for rigid steel delineator posts as specified in section 919.03, except provide posts at least 6 feet long.