

MICHIGAN
DEPARTMENT OF TRANSPORTATION

SPECIAL PROVISION
FOR
PAVEMENT MARKINGS FOR EPOXY OVERLAY AND HIGH FRICTION SURFACING
PROJECTS

PMK:MKB

1 of 1

APPR:GJD:KJK:04-08-25
FHWA:APPR:04-11-25

a. Description. This work consists of furnishing and installing pavement markings on projects that include new epoxy overlay or high friction surfacing. Ensure all construction is in accordance with this special provision, the project plans, the standard specifications, the PAVE-900 Series, and as directed by the Engineer.

b. Materials. Furnish material from the Qualified Products List (811.03D1, 811.03D2, 811.03D3).

c. Construction. After construction of an epoxy overlay or high friction surfacing, ensure the first application of longitudinal pavement markings is either Pavt Mrkg, Waterborne, __ inch, (color); Pavt Mrkg, Regular Dry, __ inch, (color); or Pavt Mrkg, Wet Reflective, Type NR, Paint, __ inch, (color), Temp. Allow the surface to wear for a minimum of 14 days, then install the 2nd application or other final pavement marking material and any required special pavement markings in accordance with the project plans and subsection 811.03 of the Standard Specifications for Construction. Do not place recessed pavement markings on bridge decks.

d. Measurement and Payment. The completed work, as described, will be measured and paid for using the associated pay items.