

CONDUCTOR COLOR	7/C	12/C	16/C	20/C
GREEN	A Ø GREEN	A Ø GREEN	A Ø GREEN	A Ø GREEN
ORANGE	A Ø YELLOW	A Ø YELLOW	A Ø YELLOW	A Ø YELLOW
RED	A Ø RED	A Ø RED	A Ø RED	A Ø RED
WHITE W/ BLACK TRACER	B Ø GREEN	B Ø GREEN	B Ø GREEN	B Ø GREEN
BLUE	B Ø YELLOW	B Ø YELLOW	B Ø YELLOW	B Ø YELLOW
BLACK	B Ø RED	B Ø RED	B Ø RED	B Ø RED
WHITE	COMMON	COMMON	COMMON	COMMON
GREEN W/ BLACK TRACER		C Ø GREEN	C Ø GREEN	C Ø GREEN
ORANGE W/ BLACK TRACER		C Ø YELLOW	C Ø YELLOW	C Ø YELLOW
RED W/ BLACK TRACER		C Ø RED	C Ø RED	C Ø RED
BLUE W/ BLACK TRACER		CASE SIGN COMMON	CASE SIGN COMMON	CASE SIGN COMMON
BLACK W/ WHITE TRACER		CASE SIGN	CASE SIGN	CASE SIGN
GREEN W/ WHITE TRACER			W-1	W-1
RED W/ WHITE TRACER			DW-1	DW-1
BLUE W/ WHITE TRACER			W-2	W-2
BLACK W/ RED TRACER			DW-2	DW-2
WHITE W/ RED TRACER				D Ø GREEN
ORANGE W/ RED TRACER				D Ø YELLOW
BLUE W/ RED TRACER				D Ø RED
RED W/GREEN TRACER				FLASHING YELLOW

WHEN USING CABLES FOR PEDESTRIAN SIGNALS, USE GREEN & RED FOR **W-1** WALK AND DON'T WALK, AND USE WHITE W/ BLACK TRACER AND BLACK FOR **W-2** WALK AND DON'T WALK

NOT TO SCALE

File: PW:RD/TR/Signals/Web/WC SD/Final

Rev. 10/21/14



PREPARED BY
TRAFFIC AND SAFETY

DRAWN BY:
CHECKED BY:

ENGINEER OF DELIVERY

ENGINEER OF DEVELOPMENT

FHWA APPROVAL DATE

MICHIGAN DEPARTMENT OF TRANSPORTATION
BUREAU OF HIGHWAYS DELIVERY STANDARD PLAN FOR
**COLOR CODE FOR WIRING
CONNECTING SIGNAL LAMPS**

PLAN DATE

WC-026-B

SHEET
1 of 1