



Notes:

DDI MARKING DETAILS

1. See PAVE-900 for arrow and legend details.
2. Use ONLY legends in conjunction with arrows on off-ramps.
3. For off-ramps use a 6" width solid white channelizing line between lanes that will turn in the same direction, and a 12" width solid white channelizing line between lanes that will turn in opposite directions.
4. When the on-ramp entrance is a drop lane, use turn arrows and ONLY legends in the tangent/weave section before the ramp curves off. Do not place the arrows or legends on the ramp itself.

NOT TO SCALE

<p>PREPARED BY TSMD DIVISION</p> <p>DRAWN BY: <u>MKB</u></p> <p>CHECKED BY: <u>CMW</u></p>	<p>DEPARTMENT DIRECTOR Paul C. Ajegba</p> <p>APPROVED BY: <u>Gregg Brunner, P.E.</u> Gregg Brunner Nov 2 2020 12:02 PM DIRECTOR, BUREAU OF FIELD SERVICES</p> <p>APPROVED BY: <u>Bradley C. Wiefelrich</u> Bradley C. Wiefelrich Oct 29 2020 4:30 PM DIRECTOR, BUREAU OF DEVELOPMENT</p>	<p>MICHIGAN DEPARTMENT OF TRANSPORTATION BUREAU OF DEVELOPMENT STANDARD PLAN FOR DIVERGING DIAMOND INTERCHANGE (DDI) PAVEMENT MARKINGS</p>	
	<p>APPROVED BY: <u>09/21/20</u> F.H.W.A. APPROVAL</p>	<p>APPROVED BY: <u>03/25/20</u> PLAN DATE</p>	<p>PAVE-928-A</p>