





KEY

-  LIGHTED ARROW PANEL (CAUTION MODE)
-  TRAFFIC FLOW
-  SHADOW VEHICLE
-  WORK VEHICLE

NOTES

1. IF A LIGHTED ARROW PANEL IS USED, IT SHALL BE IN CAUTION MODE.
2. THE SIGN(S) SHOULD BE PLACED PRIOR TO WORK AREA TO INDICATE TO THE PUBLIC THAT A SURVEY CREW IS IN THE AREA. THE ADVANCED SIGNAGE SHOULD BE WITHIN 2 MILES OF THE SURVEY AREA.
3. WHERE PRACTICAL AND WHEN NEEDED, THE WORK AND SHADOW VEHICLES SHOULD PULL OVER PERIODICALLY TO ALLOW VEHICULAR TRAFFIC TO PASS.

STANDARD NOTES

(SEE 102-GEN-NOTES)

GENERAL: G1, G2, G3, G4
 SIGNING: S1
 MAINT & SURV: MS1, MS2, MS3, MS4, MS5, MS6

NOT TO SCALE

	SURVEYING MAINTAINING TRAFFIC TYPICAL	DURATION: SHORT DURATION MOBILE	MOBILE OPERATION ON A TWO-LANE ROADWAY WITHIN 150 FEET OF WORK VEHICLE	DATE: MAY 2021
				NO: 5403-S-NFW-2L
FILE: 5403-S-NFW-2L.dgn				SHEET: 1 OF 1