Sheet 1 of 2

Top of Case Sign

Hole Opening for Chase Nipple

Holes for connection to bottom of T.S. (4 required)

Chase nipple

Lock nut

ALTERNATE SIGNAL JOINER DETAIL

Entrance head

Plastic bushing to be securely installed.

1/4" steel set screw with cup point

1 1/2" Heavy Duty lock nut

1 1/2" rigid metal nipple (length as needed)

Heavy Duty lock nut

Lock Nut

Alum Serrated Washer

Lock Nut

SS Washer

SS Cotter Pin

1-Way, 1 section 12" T.S. (Alum.)

1 Way, 12"x27" Case Sign

Stainless steel hex bolt 10-32 with flat washer & hex head nut (field drilled 4 required)

Signal Joiner

T.S. MOUNTED ON CASE SIGN

NOT TO SCALE

File: RefDoc/TR/Signals/Web/Sp Det/Fin/SIG312A.dgn   Rev. 02/16/17

Sheet 2 of 2

Entrance head

Plastic bushing to be securely installed. signal nut with recess down.

1/4" stainless steel set screw with cup point

Lock Nut

1 1/2" rigid metal nipple (length as needed)

Iron cross

Lock Nut

Iron cross (typ.)

Aluminum caps (typ)

Aluminum caps (typ)

Serrated Washer (Alum.)

Serrated Washer (Alum.)

1-Way, 1-section 12" T.S. (Alum.)

1-Way, 1-Section 12" T.S. (Alum.)

Lock Nut

Serrated Washer (Alum.)

Serrated Washer (Alum.)

Aluminum caps (typ)

Aluminum caps (typ)

Iron cross

Lock Nut

Yoke with 6" nipple. nut outside spider. top & bottom

1 1/2" Threaded Metal Hub Plate with Set Screw

Case Sign (36"x36" or 24"x30") (use blank out face when required)

NOT TO SCALE