



ACCESSIBLE MARKINGS

INTERSECTION TYPE	"Z"(FT)	
NO TRAFFIC CONTROL NO CROSSWALK	15	
NO TRAFFIC CONTROL WITH CROSSWALK	20	
TRAFFIC CONTROL PRESENT	30	
SEE SECTION 257.674 OF THE MICHIGAN VEHICLE CODE FOR MORE INFORMATION.		

NOTES:

- 1. All parking zone markings shall be retroreflective 4 inch white. 4 inch blue may supplement the white zone marking for an accessible stall.
- 2. For mid-block driveway. clearance from parking stall to the curb cut shall be 20 ft minimum.
- 3. The use of a yellow (or other color) painted curb to denote a no parking zone is optional, and shall only be used to supplement standard signs.
- 4. On-street parking for state trunk lines through municipalities shall be one of the three types illustrated.
- 5. Type II on-street parking zone markings shown this sheet. Type I or III may also be used.

NOT TO SCALE				
MICHIGAN DEPARTMENT OF TRANSPORTATION	09/21/20	03/25/20	PAVE -955-C	SHEET
BURFAU OF DEVELOPMENT STANDARD PLAN	C H M A ADDODVAL	OLAN DATE	1 A & L 333 C	2 OF 2