

## LEFT TURN STORAGE LANE(S) MARKING DETAILS







### LEFT TURN ARROW PLACEMENT FOR STORAGE LENGTHS GREATER THAN 350 FT

#### NOTES:


- 1. Where the storage length is greater than 350 ft, use a minimum of three arrows. Place additional arrows as directed by the Engineer. Arrows should be evenly spaced throughout the available length with a minimum spacing of 100 ft.
- Arrows shall be used in exclusive turn lanes at signalized intersections. When used, they shall be located as shown.
- 3. A 4 inch yellow left turn edge line may be used adjacent to raised curbs or medians in a left turn lane.




# DOUBLE LEFT TURN STORAGE LANES MARKING DETAILS



### THROUGH LANE BECOMES EXCLUSIVE LEFT TURN LANE



### THROUGH LANE BECOMES OPTIONAL LEFT TURN LANE



#### NOTES:

#### DUAL DEVELOPED LEFT TURN LANES

- Mhere at least one through lane becomes an exclusive turn lane, arrow and legend markings shall be used. Otherwise, omit the legend markings.
- 2. For double left turn lanes 280 ft or less, omit the second set of arrow-legend pairs and/or combination arrows in each lane.
- 3. When two or more arrow/legend sets are used and spacing between sets is less than "D", the Engineer may choose to reduce the distance between the arrow and legend.
- 4. Include a dotted turning guideline for all double turn movements. NOT TO SCALE

MICHIGAN DEPARTMENT OF TRANSPORTATION
BUREAU OF DEVELOPMENT STANDARD PLAN


09/21/20

03/25/20 PAVE -935-E

SHEET 2 OF 6


## LIMITED LENGTH LEFT TURN LANES

#### FOR SIGNALIZED INTERSECTIONS



#### 355 FT OR LESS OF FULL WIDTH CENTER LANE FOR LEFT TURNS

\* REMAINDER OF 5 LANE SECTION TO BE MARKED AS A BI-DIRECTIONAL LEFT TURN LANE (SEE SHEET 5)



# FOR FULL WIDTH CENTER LEFT TURN LANES GREATER THAN 355 FT

NOT TO SCALE


MICHIGAN DEPARTMENT OF TRANSPORTATION
BUREAU OF DEVELOPMENT STANDARD PLAN

09/21/20


03/25/20 PLAN DATE PAVE -935-E

SHEET 3 OF 6

# <u>LEFT TURN LANE TREATMENTS BETWEEN</u> <u>URBAN SIGNALIZED INTERSECTIONS</u>



### WHERE DISTANCE BETWEEN ADJACENT INTERSECTIONS IS 600 FT OR LESS



## WHERE DISTANCE BETWEEN ADJACENT INTERSECTIONS IS GREATER THAN 600 FT

\* LENGTH DETERMINED BY TRAFFIC COUNT ANALYSIS

NOT TO SCALE


MICHIGAN DEPARTMENT OF TRANSPORTATION
BUREAU OF DEVELOPMENT STANDARD PLAN

09/21/20 F.H.W.A. APPROVAL


03/25/20 PLAN DATE

PAVE -935-E


SHEET 4 OF 6



## TWO-WAY LEFT-TURN LANE MARKINGS



## CONVENTIONAL MARKINGS AT STOP CONTROLLED INTERSECTIONS



## ALTERNATE MARKINGS AT STOP CONTROLLED INTERSECTIONS

NOT TO SCALE				
MICHIGAN DEPARTMENT OF TRANSPORTATION	09/21/20	03/25/20	PAVE -935-E	SHEET
BUREAU OF DEVELOPMENT STANDARD PLAN	F.H.W.A. APPROVAL	PLAN DATE	ן היר שיין	6 OF 6