



## SPUI MARKING DETAILS

### Notes:

1. See PAVE-900 for arrow and legend details.
2. See PAVE-935 and PAVE-940 for non-ramp turn lane markings.
3. Use ONLY legends in conjunction with arrows on off-ramps.
4. Use turning guide lines for all turning movements. Refer to PAVE-907 for details.
5. For off-ramps use a 6" width solid white channelizing line between lanes that will turn in the same direction, and a 12" width solid white channelizing line between lanes that will turn in opposite directions.

NOT TO SCALE



PREPARED BY  
TSMD DIVISION

DRAWN BY: MKB

CHECKED BY: CMW

DEPARTMENT DIRECTOR  
Paul C. Ajegba

APPROVED BY: Gregg Brunner, P.E. Gregg Brunner  
DIRECTOR, BUREAU OF FIELD SERVICES  
Nov 2 2020 12:08 PM

APPROVED BY: Bradley C. Wiefelrich  
DIRECTOR, BUREAU OF DEVELOPMENT  
Bradley C. Wiefelrich  
Nov 5 2020 5:48 AM

MICHIGAN DEPARTMENT OF TRANSPORTATION  
BUREAU OF DEVELOPMENT STANDARD PLAN FOR

## SINGLE POINT URBAN INTERCHANGE (SPUI) PAVEMENT MARKINGS

09/21/20  
F.H.W.A. APPROVAL

03/25/20  
PLAN DATE

PAVE-927-A

SHEET  
1 OF 1