



SINGLE LANE PARELLEL EXIT/ENTRANCE RAMP DETAILS

Notes:

- 1. For additional placement information, see PAVE-900, PAVE-905, PAVE-907, PAVE-925, PAVE-940, and R-127.
- Installation of the wrong way arrow is required. Installation of the stop bar is required at signalized intersections. All other features are optional and shall be installed at the direction of the Engineer.
- 3. When individual reflectors are used, they shall be placed at 10' maximum spacing. If a proprietary delineation system is used, install per the Manufacturer's recommendations and as directed by the Engineer.





MULTILANE PARALLEL EXIT/ENTRANCE RAMP DETAILS

Notes:

- 1. For additional placement information, see PAVE-900, PAVE-905, PAVE-907, PAVE-925, PAVE-940, and R-127.
- Installation of the wrong way and lane use arrows are required. Installation of the stop bar is required at signalized intersections. All other features are optional and shall be installed at the direction of the Engineer.
- 3. When individual reflectors are used, they shall be placed at 10' maximum spacing. If a proprietary delineation system is used, install per the Manufacturer's recommendations and as directed by the Engineer.

NOT TO SCALE

MICHIGAN DEPARTMENT OF TRANSPORTATION
BUREAU OF DEVELOPMENT STANDARD PLAN

09/21/20 F.H.W.A. APPROVAL

03/25/20 PAVE -926-B

SHEET 2 OF 2