



NOTE: GALVANIZED STEP IS STANDARD WITH GRADE RING ASTM C478.





N.T.S. DETAIL - GRADE RING WITH 39 IN I.D. & 46 1/2" RECESS

| | LENGTH | WIDTH | HEIGHT |
|----------------------------------|----------|----------|----------|
| INSIDE OUTSIDE RECOMMENDED | 48 58 | 48 58 | 48 58 |
| HOLE SIZE | 82 | 82 | _ |

| MIN THICKNESS | | MIN WEIGHT LBS | |
|---------------|---|----------------|------|
| WALL | 5 | · | |
| ROOF | 5 | TOP | 3300 |
| FLOOR | 5 | BOTTOM | 3850 |
| | | TOTAL | 7150 |

DETAIL - 4FT X 4FT X 4FT PRECAST CONCRETE HANDHOLE
N.T.S.


| Michigan Department of Transportation | |
|---------------------------------------|----|
| DEPARTMENT DIDECTOR | (S |

STANDARD PLAN FOR
HANDHOLE - PRECAST
POLYMER CONCRETE


DEPARTMENT DIRECTOR BRADLEY C. WIEFERICH, PE (SPECIAL DETAIL) 07/06/23 FHWA APPROVAL PLAN DATE SIG-240-A


SHEET 4 OF 6 SECT

ECI



CONCRETE: 4500 P.S.I. @ 28 DAYS REINFORCEMENT: GRADE 60 REBAR ALL BARS ARE #4






S DETAIL PLANVIEW

N.T.S.







| EVIDOT chigan Department of Transportation | | |
|--|------------------|---|
| DEPARTMENT DIRECTOR | (SPECIAL DETAIL) | ſ |
| BRADLEY C. WIEFERICH, PE | EUWA ADDDOVAL | ı |

STANDARD PLAN FOR
HANDHOLE - PRECAST
POLYMER CONCRETE

(SPECIAL DETAIL) 07/06/23 SIG-240-A

SHEET 6 OF 6 SECT

SEC