

2025 MMUTCD Changes to the 11th Federal Edition
December 2025

PART: Cover

CHANGES:

Part	Original Page Number	Final Page Number	Paragraph Number	Change
Cover	N/A	N/A	N/A	Revise to include Michigan Department of Transportation (MDOT), Michigan State Police (MSP), and Federal Highway Administration (FHWA) logos.
Cover	N/A	N/A	N/A	Add "2025 Michigan MUTCD" under title as first line, second line "11th Federal Edition".

2025 MMUTCD Changes to the 11th Federal Edition
December 2025

PART: Introduction

CHANGES:

Part	Original Page Number	Final Page Number	Paragraph Number	Change
Introduction	N/A	N/A	N/A	Add Certification letter.
Introduction	N/A	N/A	N/A	Add Introduction to Michigan Edition

2025 MMUTCD Changes to the 11th Federal Edition
December 2025

PART: Part 1

CHANGES:

Part	Original Page Number	Final Page Number	Paragraph Number	Change
1A.02	1	1	01	Delete Paragraph 01 text and insert "Traffic control devices includes all signs, signals, markings, and devices placed or erected by authority of a public body or official having jurisdiction, for the purpose of regulating, warning, or guiding traffic. MCL 257.70"
1A.05	3	3	01	Replace "Standard Highway Signs" with "Michigan Standard Highway Signs." Replace "FHWA" with "MDOT".
1A.05	3	3	02	Delete Paragraph 02 text and insert "For information about the "Michigan Standard Highway Signs" publication, visit the MDOT website at http://www.michigan.gov/MDOT . All references in the manual to the Standard Highway Signs publication will pertain to the Michigan version."
1A.06	3	3	02	Revise "Guidance" to "Support". Delete Paragraph 02 text and insert "The "Michigan Vehicle Code" (MVC) contains motor vehicle codes and traffic laws for use in Michigan. The MVC takes precedent over the UVC. Where appropriate, sections from Michigan State Statute, including the MVC, have been added to this manual. All references from the MVC may not be current; therefore, current Michigan State Statute takes precedent."
1B.01	4	4	03A	Insert new Support paragraph 03A: "Michigan State Statute has the following provision for traffic control devices on private roads open to the general public." Insert MCL 257.601a.
1B.01	4	5	05	Insert the following text at the end of Paragraph 05: "Michigan State Statute has the following provision for traffic control devices in parking areas." Insert MCL 257.942b.
1B.02	4	5	04	Add Support paragraph 04 "Michigan State Statute has the following provision for adoption of a uniform manual." Insert MCL 257.608.
1B.06	9	10	04	Replace "this" with "the National".
1B.07	9	10	01	Replace "this" with "the National".
1B.07	11	12	04	Replace "this" with "the National".
1B.07	11	12	08	Replace "this" with "the National".

Part	Original Page Number	Final Page Number	Paragraph Number	Change
1C.02	13	14	01	Delete "Uniform" and insert "Michigan" Insert "Michigan Compiled Law," after "AASHTO Transportation Glossary (Highway Definition),"
1C.02	16	17	03	Revise Definition 61 from "Diagnostic Team" to "Diagnostic Study Team." Revise definition from "a group of knowledgeable representatives of the parties of interest in a grade crossing or group of grade crossings (see 23 CFR Part 646.204)" to "a group of knowledgeable individuals from the Department of Transportation, road authorities, railroads, and others who meet and, using crossing safety management principles, evaluate conditions at proposed or existing crossings and assist the Department of Transportation in making determinations concerning safety needs. MCL 462.105."
1C.02	16	17	03	Add the following text at the end of the definition for 64. Driving Aisle: "However, MCL 257.942b states that a sign or other traffic control device in a parking area shall conform to the requirements of the Michigan manual of uniform traffic control devices (see Section 1B.01)."
1C.02	17	18	03	Add the following text at the end of the definition for 85. Flagger: "In Michigan, the term "Traffic Regulator" is synonymous with "Flagger.""
1C.02	18	19	03	Insert after Definition 96 for Grade Crossing: "Public grade crossing means the point at which any railroad intersects with any public street or highway, or a nonmotorized trail. MCL 462.105(8). Private crossing means any at-grade intersection of a railroad with any traveled way not under the jurisdiction of a road authority. MCL 462.107(6)."
1C.02	19	20	03	Remove text after 104. HOV Lane and insert "any designated lane or ramp on a highway designated for the exclusive or preferential use of a public transportation vehicle or private motor vehicles carrying no fewer than a specified number of occupants, including the driver of the vehicle. MCL 257.20c."
1C.02	22	23	03	Remove text after "156. Parking Area" and insert: "an area used by the public as a means of access to and egress from, and for the free parking of motor vehicles by patrons of a shopping center, business, factory, hospital, institution, or similar building or location. MCL 257.941."
1C.02	24	25	03	Remove text after "210. School" and insert "an educational institution operated by a local school district or by a private, denominational, or parochial organization. School does not include an educational institution that the department of education determines has its entire student population in residence at the institution or to which all students are transported in motor vehicles. MCL 257.627a(1)(b)."

Part	Original Page Number	Final Page Number	Paragraph Number	Change
1C.02	24	25	03	Insert as Definition 210a "School Crossing – a crosswalk designated by the department of state highways and transportation, a county road commission, or a local authority as a place to be used by school children for crossing a street or highway. MCL 257.57a."
1C.02	24	25	03	Insert as Definition 210b "School Crossing Guard – a person 17 years of age or older authorized to supervise children using a school crossing. MCL 257.57b."
1C.02	24	25	03	Insert as Definition 210c "School Session, Regularly Scheduled – that part of a day scheduled for student instruction until final dismissal of the student body for that day. MCL 257.627a(1)."
1C.02	24	26	03	Remove text after "211. School Zone" and insert "School Zone - school property on which a school building is located and the area adjacent to the school property that is designated by the signs per Section 7B.02. Except for a crossing as described in Section 7B.03, the school zone extends not more than 1,000 feet from the property line of the school in each direction. MCL 257.627a(1)(c)."
1C.02	28	29	03	For Item 284. Vehicle: Replace "can" with "is or may." Replace "trains and light rail transit operating in exclusive or semi-exclusive alignments." with "devices exclusively moved by human power or used exclusively upon stationary rails or tracks. MCL 257.79."
1C.03	30	31	01	Insert as Acronym 63 "MVC - Michigan Vehicle Code"
1C.03	30	31	01	Insert as Acronym 64 "MCL - Michigan Compiled Law"
1D.02	31	32	05A	Insert new Support paragraph 05A: Michigan State Statute has the following provisions regarding the responsibility and authority for traffic control devices." Insert MCL 257.609, MCL 257.610, MCL 257.942, and 390.891.
1D.02	31	34	06	Delete Paragraph 06 text and insert "Michigan State Statute has the following provisions for unauthorized placement of traffic control devices or other sign or message placed on the highway right-of-way". Insert MCL 257.615 (c) and (d) and Section 750.377D of the Michigan Penal Code.
1D.07	34	37	02A	Insert new Support paragraph 02A: "Section 1D.MI12 contains reference to Michigan State Statute regarding commercial advertising on traffic control devices."

Part	Original Page Number	Final Page Number	Paragraph Number	Change
1D.MI12	N/A	42	N/A	<p>Add New "Section 1D.MI12 (Michigan) Signs or Lights Resembling Traffic Control Devices or Emergency Vehicle Lights. Standard: No device shall be placed along a street or highway which resembles a traffic control device or lights authorized by law for emergency vehicles.</p> <p>Support: 02 The "Michigan Vehicle Code" has the following provision for signs or lights resembling traffic control devices or emergency vehicle lights:" Insert MCL 257.615 (a) and (b).</p>

2025 MMUTCD Changes to the 11th Federal Edition
December 2025

PART: Part 2A

CHANGES:

Part	Original Page Number	Final Page Number	Paragraph Number	Change
2A.23	64	68	05	Insert: "Support: Michigan law regards divided highway crossings with median widths greater than 30 feet as separate intersections. MCL 257.22(b). However, the application of signing and markings at intersections is determined through the provisions provided in this Manual. Therefore, it is acceptable for a median opening on a divided highway of median width 30 feet or greater not to be signed and marked as separate intersections if supported by the provisions of this Section."

2025 MMUTCD Changes to the 11th Federal Edition
December 2025

PART: Part 2B

CHANGES:

Part	Original Page Number	Final Page Number	Paragraph Number	Change
2B.02	67	71	01	Replace "Standard Highway Signs" with "Michigan Standard Highway Signs".
2B.03	73	77	N/A	Add "R12-5a" to the Table 2B-1 (Sheet 6 of 6).
2B.03	73	77	N/A	Delete "or" and insert "and" for R16-3 sign in Table 2B-1 (Sheet 6 of 6).
2B.06	75	79	01	Insert at end of paragraph: "MCL 257.649 within the "Michigan Vehicle Code" establishes Right of Way rules in Michigan."
2B.19	81	85	00	Insert new Support paragraph 00: "The "Michigan Vehicle Code" does not address road user responsibilities at uncontrolled crosswalks. Local municipalities often establish road user responsibilities at uncontrolled crosswalks on highways and streets within their boundaries by adopting the Uniform Traffic Code as local ordinance."
2B.19	81	85	02	Replace "Stop Here for" with "Yield Here To (Stop Here For)". After "law", insert "(local ordinance)". Replace "stop" with "yield (stop)". Replace "STATE" with "LOCAL".
2B.19	81	85	06	Replace "across an multi-lane approach" with "across a multi-lane approach"
2B.20	81	85	01	After "laws", insert "(local ordinance)". Delete "The legend STATE LAW may be displayed at the top of the R1-6 series and R1-9 series signs if applicable."
2B.20	81	85	01A	Insert new Standard: "If used, the legend LOCAL LAW shall be displayed at the top of the R1-6 series and R1-9 series signs."
2B.20	81	86	02	Insert "Option:" before Paragraph 02.
2B.20	82	86	N/A	Figure 2B-2: Replace "STATE LAW" with "LOCAL LAW" on all applicable signs. Remove "The legend STATE LAW is optional." from the * note in the figure.
2B.20	83	87	03	Replace "in States where the State law" with "where the law (local ordinance)".
2B.20	83	87	10	Delete "State Law" and replace with "local ordinance"
2B.21	84	88	02	Insert at end of paragraph: "MCL 257.627 within the "Michigan Vehicle Code" provides statutory speed limits on Michigan highways."

Part	Original Page Number	Final Page Number	Paragraph Number	Change
2B.21	84	88	03	Remove the last sentence "The engineering study will determine which of the recommended factors will prevail in setting the speed limit." from Paragraph 03.
2B.21	84	88	06A	Insert new Support paragraph 06A: "MCL 257.628 within the "Michigan Vehicle Code" provides the basis for establishing speed zones (other than statutory speed limits) on Michigan roadways. The phrase "engineering study that has been performed in accordance with traffic engineering practices" in Paragraph 6 of this Section is considered to be synonymous with the following phrases in MCL 257.628: A. Engineering and traffic investigation. B. Speed study C. Traffic engineering practices that provide an objective analysis of the characteristics of the highway. D. Engineering and safety study."
2B.21	84	89	09A	Insert new Support paragraph 09A: "MCL 257.628(5) requires speed limits to be determined in accordance with traffic engineering practices that provide an objective analysis of the characteristics of the highway and by the 85th-percentile speed. The statute allows for a speed limit to be set below the 85th-percentile speed if an engineering and safety study demonstrates a situation with hazards to public safety that are not reflected by the 85th-percentile speed, but the statute does not allow the speed limit to be set below the 50th-percentile speed."
2B.22	87	91	04	Insert new Support paragraph 04: "MCL 257.627 within the "Michigan Vehicle Code" provides for special speed limits applying to certain classes of vehicles in Michigan."
2B.23	87	91	04	Insert new Support paragraph 04: "The "Michigan Vehicle Code" does not permit the use of night speed limits."
2B.24	87	92	03	Insert new Support paragraph 03: "MCL 257.627 within the "Michigan Vehicle Code" provides for minimum speed limits applying to limited access freeways in Michigan."
2B.36	102	106	01	Insert at end of Paragraph 01 "such as a work zone."
2B.45	107	111	01A	Insert new Support paragraph 01A: "MCL 257.644(1) and MCL 257.726(2) within the "Michigan Vehicle Code" provide for vehicle exclusions in Michigan."
2B.45	108	112	03	Delete "and" after Item P. Insert items "R. AUTHORIZED VEHICLES ONLY (R5-11), S. NO MOTORCYCLES UNDER 125cc, FARM TRACTORS, SELF-PROPELLED FARM IMPLEMENTS (R5-13), and T. NO PEDESTRIANS, BICYCLES, MOTORCYCLES UNDER 125cc (R5-13a)."

Part	Original Page Number	Final Page Number	Paragraph Number	Change
2B.48	114	118	07	Replace "3 feet" with "4 feet". Delete "(see Figure 2B-17)" from Paragraph 07 and, in its place, insert "(Figure 2B-17 deleted)".
2B.49	115	119	N/A	Delete Figure 2B-17.
2B.53	126	130	27	Replace "Standard Highway Signs" with "Michigan Standard Highway Signs".
2B.60	134	138	02	Delete Guidance and insert new Standard: "When used, the NO TURN ON RED (R10-11 series) sign shall be located above or adjacent to the traffic control signal or as close as possible to the point where the turn is made, or at both locations, so that 1 or more of the signs are visible to a vehicle operator intending to turn, at the point where the turn is made. MCL 257.612(5)."
2B.60	134	138	02A	Insert new Option paragraph 02A: "An additional NO TURN ON RED (R10-11 series) sign may be used at the far side of the intersection in the direct line of vision of the turning vehicle operator. MCL 257.612(5)."
2B.60	134	138	03	Insert "Guidance:"
2B.62	136	140	N/A	Add R12-5a to Figure 2B-30.
2B.64	137	141	08	Add ", R12-5a," after "R12-5",
2B.64	138	142	13	Replace "at" with "not more than 50 feet in advance of". Insert at end of paragraph "MCL 257.631(5)."
2B.64	138	142	14A	Insert new Support paragraph 14A: "The SEASONAL LOAD AND SPEED RESTRICTIONS IN EFFECT (R12-8) sign is intended for temporary placement on highways with maximum axle load and speed limit reductions during the spring in accordance with MCL 257.722 within the "Michigan Vehicle Code.""
2B.64	138	142	14B	Insert new Option paragraph 14B: "During periods of restriction, the SEASONAL LOAD AND SPEED RESTRICTIONS IN EFFECT (R12-8) sign may be installed at intersections or other locations deemed appropriate by the road authority."
2B.66	138	142	03	Insert new Support paragraph 03: "MCL 257.726 within the "Michigan Vehicle Code" provides for truck route designations in Michigan."
2B.69	140	144	00	Insert new Support paragraph 00: "Michigan state statute permits the use of photo enforcement cameras at highway-rail grade crossings and in some work zones. Sections 2C.69 and 6G.08 provide additional requirements, respectively."

Part	Original Page Number	Final Page Number	Paragraph Number	Change
2B.70	140	144	00	Insert new Support paragraph 00: "MCL 257.618a within the "Michigan Vehicle Code" provides for requirements associated with removing vehicles involved in an accident from the main traveled portion of the roadway in Michigan."
2B.70	140	145	N/A	In Figure 2B-33, on the R16-3 sign, replace "MOVE OVER OR REDUCE SPEED FOR VEHICLES STOPPED ON SHOULDER" with "MOVE OVER AND REDUCE SPEED FOR STOPPED EMERGENCY AND MAINTENANCE VEHICLES".
2B.71	141	145	00	Insert new Support paragraph 00: "MCL 257.633a within the "Michigan Vehicle Code" provides for driver responsibilities when approaching and passing an emergency vehicle with its lights activated in Michigan."
2B.71	141	145	01	Replace "STATE LAW MOVE OVER OR REDUCE SPEED FOR VEHICLES STOPPED ON SHOULDER" with "STATE LAW MOVE OVER AND REDUCE SPEED FOR STOPPED EMERGENCY AND MAINTENANCE VEHICLES".
2B.72	141	145	00	Insert new Support paragraph 00: "MCL 257.602b within the "Michigan Vehicle Code" provides for restrictions associated with hand-held phone use while driving in Michigan."
2B.73	141	145	01	Insert at end of Paragraph 01 "MCL 257.684 within the "Michigan Vehicle Code" provides for headlight requirements in Michigan."
2B.74	142	146	02	Replace "Standard Highway Signs" with "Michigan Standard Highway Signs".

2025 MMUTCD Changes to the 11th Federal Edition
December 2025

PART: Part 2C

CHANGES:

Part	Original Page Number	Final Page Number	Paragraph Number	Change
2C.02	147	151	01	Change "Standard Highway Signs" to "Michigan Standard Highway Signs"
2C.05	154	158	02	Delete "J. Rumble Strips (Chapter 3K)" and re-letter "Vehicle Speed Feedback Sign (see Section 2C.13)" and "Speed Reduction Markings (see Section 3B.28)" to "J" and "K", respectively.
2C.05	154	158	03	Insert "(see Chapter 3K)" after "rumble strips". This change and the change above are to delete repetitiveness and emphasize that rumble strips are not a traffic control device.
2C.07	156	160	N/A	In Figure 2C-2, change advisory speed plaques (W13-1P and W13-1aP) to 35 mph.
2C.12	163	167	N/A	Insert "(optional)" to the W13-2 label on Figure 2C-3 (Sheet 3 of 5)
2C.13	166	170	04A	Insert "04A Support: Animated elements include word phrases, such as SLOW DOWN."
2C.18	170	174	00	Insert "00 Standard: A NARROW BRIDGE (W5-2) sign (see Figure 2C-6) shall be used in advance of any bridge or culvert having a two-way roadway clearance width less than 19 feet but more than 17 feet. Where these conditions exist for an underpass, a NARROW UNDERPASS (W5-2a) sign shall be used. MCL 254.20."
2C.18	170	174	01	Delete "having a two way roadway horizontal clearance of 16 to 18 feet, or any bridge or culvert".
2C.18	170	174	04	Delete Paragraph 04 and insert "Deleted Paragraph 04."
2C.19	170	174	00	Insert "00 Standard: A ONE LANE BRIDGE (W5-3) sign (see Figure 2C-6) shall be used in advance of any bridge or culvert having a two-way roadway clearance width of 17 feet or less. Where these conditions exist for an underpass, a ONE LANE UNDERPASS (W5-3a) sign shall be used. MCL 254.20."
2C.19	170	174	01	Delete "A. Having a roadway horizontal clearance of less than 16 feet, or". Delete "B" and insert "A". Within new A. delete "18" and insert "19". Delete "C" and insert "B". Within new B. delete "18" and insert "19".
2C.19	170	174	04	Delete Paragraph 04 and insert "Deleted Paragraph 04."
2C.19	170	174	05	Change "A, B, or C" to "A or B"

Part	Original Page Number	Final Page Number	Paragraph Number	Change
2C.25	172	176	01A	Insert "01A Support: In Michigan, MCL 257.719 within the "Michigan Vehicle Code" establishes a statutory maximum vehicle height of 13 feet 6 inches."
2C.25	172	176	02	Insert at end of paragraph, "For purposes of this sign, minimum clearance determinations should be applied over the complete usable shoulder width."
2C.25	172	176	06	Delete "Option", making the following paragraph Guidance. Within the paragraph, delete "may" and insert "should." At end of paragraph, insert "when the clearance of a structure over the roadway is 14 feet, 6 inches or less."
2C.25	172	176	07	Insert "Option:"
2C.47	186	190	N/A	Remove "pacement" and insert "placement" within Figure 2C-13 (Sheets 2, 3, and 5 of 5)
2C.60	197	201	02	Remove "6 months" and insert "12 months". This change is to maintain consistency with Section 2A.11 and Section 2C.38.
2C.69	198	202	00	Insert "00 Standard: When a highway-rail grade crossing is enforced by photographic equipment, a Photo Enforced (W16-10P) plaque or a PHOTO ENFORCED (W16-10aP) word message plaque (see Figure 2C-16) shall be mounted below the Grade Crossing Advance Warning (W10-1) sign at highway-rail grade crossings with flashing signals and gates to advise road users that the regulations associated with the crossing are being enforced by photographic equipment. MCL 257.667a."
2C.69	198	203	01	Insert "and when the "Michigan Vehicle Code" allows for photo enforcement of a specific regulation." at end of Option paragraph.

2025 MMUTCD Changes to the 11th Federal Edition
December 2025

PART: Part 2D

CHANGES:

Part	Original Page Number	Final Page Number	Paragraph Number	Change
2D.04	206	210	01	Change "Standard Highway Signs" to "Michigan Standard Highway Signs".
2D.05	208	212	02	Change "Standard Highway Signs" to "Michigan Standard Highway Signs".
2D.07	211	215	N/A	In the ** note below Table 2D-2, change "Standard Highway Signs" to "Michigan Standard Highway Signs".
2D.08	213	217	01	Change "Standard Highway Signs" to "Michigan Standard Highway Signs".
2D.08	214	218	N/A	In Figure 2D-3, change "Standard Highway Signs" to "Michigan Standard Highway Signs" in the note.
2D.08	215	219	26	Change "Standard Highway Signs" to "Michigan Standard Highway Signs".
2D.09	216	220	05	Delete "Paragraph 6" and insert "Paragraph 7".
2D.11	216	220	01	Change "Standard Highway Signs" to "Michigan Standard Highway Signs" in two instances.
2D.11	216	220	02	Delete "and M1-1a".
2D.11	217	221	N/A	For Figure 2D-4, delete M1-1a signs, replace M1-5 sign pictorials with Michigan's State Route sign., and replace "16" within M1-6 sign with "F4".
2D.11	217	221	04	Delete Option. Replace with "Deleted Paragraph 04."
2D.11	217	221	05	Delete Standard. Replace with "Deleted Paragraph 05."
2D.11	218	222	11	Change "Standard Highway Signs" to "Michigan Standard Highway Signs".
2D.11	218	222	17	Change "Standard Highway Signs" to "Michigan Standard Highway Signs".
2D.15	219	223	N/A	For Figure 2D-5, replace "21" pictorial within the M2-2 sign with Michigan State Route symbol.
2D.37	236	240	10	Replace "an" with "a".
2D.41	239	243	N/A	For Figure 2D-11, replace "7" and "3" pictorials within the D1-1e and D1-5a signs with the Michigan State Route symbol.
2D.43	243	247	N/A	In Figure 2D-12 on Sheet 4 of 4, change the overhead sign support to be a truss instead of a cantilever.

Part	Original Page Number	Final Page Number	Paragraph Number	Change
2D.44	244	248	N/A	In Figure 2D-13 on Sheet 1 of 3, revise the "RIGHT TURN ONLY" sign to be a "TURN RIGHT ONLY" (R4-21 modified) sign.
2D.44	245	249	N/A	In Figure 2D-13 on Sheet 2 of 3, change the overhead sign supports to be trusses instead of cantilevers in two instances.
2D.45	247	251	N/A	For Figure 2D-14, replace "124" pictorial within the D3-1a sign with the Michigan State Route symbol.

2025 MMUTCD Changes to the 11th Federal Edition
December 2025

PART: Part 2E

CHANGES:

Part	Original Page Number	Final Page Number	Paragraph Number	Change
2E.01	289	293	02	Change "Standard Highway Signs" to "Michigan Standard Highway Signs".
2E.12	297	301	06	Change "Standard Highway Signs" to "Michigan Standard Highway Signs".
2E.12	297	301	N/A	Change "Standard Highway Signs" to "Michigan Standard Highway Signs" in the notes below Tables 2E-2, 2E-3, 2E-4, and 2E-5.
2E.12	298	302	9	Change "Standard Highway Signs" to "Michigan Standard Highway Signs".
2E.14	301	305	03	Change "Standard Highway Signs" to "Michigan Standard Highway Signs".
2E.18	302	306	07	Change two instances of "Standard Highway Signs" to "Michigan Standard Highway Signs".
2E.21	305	309	N/A	In Figure 2E-2, change dimension on bottom graphic from 1/2 mile to 1 mile in two instances.
2E.39	344	348	02	Delete "either" after "expressways,".
2E.40	347	351	09	Change "Standard Highway Signs" to "Michigan Standard Highway Signs".
2E.40	352	356	N/A	Figure 2E-39: Add EXIT ONLY plaque beneath "I-695 South Camden" sign located at theoretical gore shown in the figure.
2E.40	353	357	N/A	Figure 2E-40: Add EXIT ONLY plaque beneath "To 23 Business Penniman" sign located at theoretical gore shown in the figure.
2E.41	356	360	07	Change "Standard Highway Signs" to "Michigan Standard Highway Signs".
2E.54	370	374	11	Change "Standard Highway Signs" to "Michigan Standard Highway Signs".
2E.55	373	377	02	Change "Standard Highway Signs" to "Michigan Standard Highway Signs".

2025 MMUTCD Changes to the 11th Federal Edition
December 2025

PART: Part 2F

CHANGES:

Part	Original Page Number	Final Page Number	Paragraph Number	Change
2F.12	393	397	N/A	In Figure 2F-10, change "Standard Highway Signs" to "Michigan Standard Highway Signs" under the arrow diagram.

2025 MMUTCD Changes to the 11th Federal Edition
December 2025

PART: Part 2G

CHANGES:

Part	Original Page Number	Final Page Number	Paragraph Number	Change
2G.24	455	459	04	Insert "a" to the first sentence here: When part-time travel on <u>a</u> shoulder..."
2G.24	455	459	07	Insert "A sequential chevron may be used in place of a Yellow X as described in paragraph 4 of this Section."
2G.25	455	459	02A	Insert "A sequential chevron may be used in place of a Yellow X as described in paragraph 2 of this Section when vacating the lane can only be accomplished by merging to one specific side of the lane being vacated."
2G.26	457	461	03	Change "Standard Highway Signs" to "Michigan Standard Highway Signs".

2025 MMUTCD Changes to the 11th Federal Edition
December 2025

PART: Part 2H

CHANGES:

Part	Original Page Number	Final Page Number	Paragraph Number	Change
2H.10	464	468	03	Remove "I2-3 or".
2H.10	464	468	04	Change "the I2-3 or" to "an" and add "as an alternate to overhead." to the end of the paragraph.
2H.13	470	474	16, 16B	Change "Standard Highway Signs" to "Michigan Standard Highway Signs".

2025 MMUTCD Changes to the 11th Federal Edition
December 2025

PART: Part 2I

CHANGES:

Part	Original Page Number	Final Page Number	Paragraph Number	Change
2I.02	475	481	N/A	In Table 2I-1 on Sheet 2 of 2, change "Standard Highway Signs" to "Michigan Standard Highway Signs" in notes.
2I.03	482	486	26	Font for this paragraph in national manual was bold, but it is worded as optional and is located under the Optional heading. Unbold the paragraph.

2025 MMUTCD Changes to the 11th Federal Edition
December 2025

PART: Part 2J

CHANGES:

Part	Original Page Number	Final Page Number	Paragraph Number	Change
2J.02	495	499	N/A	Figure 2J-2: Relocate leader line for FOOD-EXIT 44 sign to the sign symbol below.
2J.12	504	508	03	Add Standard: Specific service signs on the state highway system shall be in accordance with Michigan State Statutes 252.52 and 257.676a.

2025 MMUTCD Changes to the 11th Federal Edition
December 2025

PART: Part 2K

CHANGES:

Part	Original Page Number	Final Page Number	Paragraph Number	Change
2K.03	506	510	02	Change "Standard Highway Signs" to "Michigan Standard Highway Signs" .
2K.07	509	513	03	Add Standard: Tourist-oriented directional signs on the state highway system shall be in accordance with Michigan State Statutes 247.401, 247.402, 247.403, 247.404, and 247.405.

2025 MMUTCD Changes to the 11th Federal Edition
December 2025

PART: Part 2L

CHANGES:

Part	Original Page Number	Final Page Number	Paragraph Number	Change
2L.01	510	514	08	Change "Standard Highway Signs" to "Michigan Standard Highway Signs" .
2L.05	516	520	11	Delete Paragraph 11 , Table 2L-3 and Table 2L-4, and insert "Deleted Paragraph 11, Table 2L-3 and Table 2L-4."
2L.06	516	520	02	Delete "If both a travel time and a distance are displayed, the sign should display only one destination." and add "If travel times are displayed via the route on which the sign is located, the sign should display no more than two destinations. If travel times to the same destination via different routes are displayed, the sign should display only one destination."

2025 MMUTCD Changes to the 11th Federal Edition
December 2025

PART: Part 2M

CHANGES:

Part	Original Page Number	Final Page Number	Paragraph Number	Change
2M.07	522	524	01	Change "Standard Highway Signs" to "Michigan Standard Highway Signs" .
2M.10	530	532	08	Change "Standard Highway Signs" to "Michigan Standard Highway Signs" .

2025 MMUTCD Changes to the 11th Federal Edition
December 2025

PART: Part 2N

CHANGES:

Part	Original Page Number	Final Page Number	Paragraph Number	Change
2N	N/A	N/A	N/A	No changes.

2025 MMUTCD Changes to the 11th Federal Edition
December 2025

PART: Part 3

CHANGES:

Part	Original Page Number	Final Page Number	Paragraph Number	Change
3A.04	538	540	06A	Insert new Support paragraph 06A: "In Michigan, a broken line with a 12.5-foot line segment and a 37.5-foot, which meets the ratio permitted in Paragraph 06 of this Section, is typically used."
3A.04	538	540	07	Insert "Guidance".
3A.04	538	540	07	Change "3" to "5" and change "9" to "20". Insert "or dimensions in a similar ratio of line segments to gaps as appropriate for traffic speeds and the need for delineation" at the end of the first sentence.
3A.04	538	540	07A	Insert new Support 07A: "In Michigan, a dotted line for line extensions within an intersection, taper area, or interchange ramp area consisting of 2-foot line segments and 4-foot gaps is typically used."
3B.01	540	542	07	Delete "Guidance" and insert "Support". Change Paragraph 07 to be support text.
3B.01	540	542	08	Insert "Guidance" before Paragraph 08.
3B.05	543	545	01A	Insert new Support 01A: "MCL 257.642(1)(c) within the "Michigan Vehicle Code" provides allowances and prohibitions for vehicle operations within a two-way left turn lane."
3B.07	553	555	11	Change "3" to "5" and "9" to "20".
3B.11	563	565	03A	Insert new Support paragraph 03A: "In Michigan, dotted lane line extensions within an intersection consisting of 2-foot line segments and 4-foot gaps are typically used." Insert "Guidance" before Paragraph 04.
3B.12	567	569	N/A	In Figure 3B-14, replace the W9-1 sign assembly with a W4-2 sign at the "AP" distance. Remove the W4-2R sign at the beginning of the taper.
3B.13	569	571	N/A	In Figure 3B-15, Sheet 1 of 2, add "Optional" with leader line to diagonal markings.
3B.13	570	572	N/A	In Figure 3B-15, Sheet 2 of 2, add "Optional" with leader line to chevron markings.
3B.19	573	575	03	Delete "State law" and insert "local ordinance".
3B.20	575	577	05	Change "Standard Highway Signs" to "Michigan Standard Highway Signs".

Part	Original Page Number	Final Page Number	Paragraph Number	Change
3B.22	576	578	N/A	In Figure 3B-18, revise images D and E to show Michigan state route marker. Also, change "Standard Highway Signs" to "Michigan Standard Highway Signs" in figure note.
3B.22	577	579	N/A	In Figure 3B-19, change "Standard Highway Signs" to "Michigan Standard Highway Signs" in figure note.
3B.25	579	581	N/A	In Figure 3B-21, change "Standard Highway Signs" to "Michigan Standard Highway Signs" in figure note.
3B.23	580	582	N/A	In Figure 3B-22, add "*" on diagonal markings in the figure to indicate they are optional. Also, bottom align all arrows in the same position across lanes.
3B.27	582	584	N/A	Figure 3B-23: Left drawing - insert heading "No Intersection Traffic Control with Crosswalk", delete stop line and move dimension to first crosswalk line. Delete "30" and insert "20". Delete "on approaches controlled by STOP (or YIELD) signs per UVC" and insert "from crosswalk per MCL 257.674(1)(f)". Delete "per UVC" from bottom dimension. Middle drawing - insert heading "Traffic Signal, Stop Sign, or Flashing Beacon", delete "approaches controlled by traffic control signals per UVC" and insert "approaches per MCL 257.674(1)(g)". Delete "per UVC" from bottom dimension. Right drawing - insert heading "No Intersection Traffic Control with No Crosswalk", delete "Sidewalk" label and drawing of sidewalk. Delete "20" and insert "15", delete "marked or unmarked crosswalks at intersections per UVC" and insert "intersection of property lines at an intersection of highways per MCL 257.674(1)(f)". Delete "per UVC" from bottom dimension. Add dashed property line to give a point of reference, and label it as "Property Line".
3D.06	605	607	08	Change "Standard Highway Signs" to "Michigan Standard Highway Signs".

2025 MMUTCD Changes to the 11th Federal Edition
December 2025

PART: Part 4

CHANGES:

Part	Original Page Number	Final Page Number	Paragraph Number	Change
4A.02	643	645	01	Delete "Uniform" and insert "Michigan"
4A.02	643	645	01	Delete ", the standards for the meanings of separate bicycle signal face indications as provided in Section 4A.05,"
4A.02	643	645	01	Insert at end of paragraph: "The "Uniform Vehicle Code" is the primary source for the standards for the meanings of separate bicycle signal face indications as provided in Section 4A.05."
4A.03	643	645	00	Insert new Support paragraph 00: "Sections 257.612(1) and 257.613(1) of the "Michigan Vehicle Code" provide meanings to steady vehicular signal indications for vehicle operators and for pedestrians, respectively. Paragraph 01 of this Section has been modified to reflect the "Michigan Vehicle Code.""
4A.03	643	645	01	Delete "is permitted to proceed straight through or turn right or left or make a U-turn movement except as such movement is modified by lane use signs, turn prohibition signs, lane markings, roadway design, separate turn signal indications, or other traffic control devices." from the first sentence of A.1 and insert "may proceed straight through or turn right or left unless a sign at that place prohibits either turn."
4A.03	643	645	01	Delete "or making a U-turn movement" from the second sentence of A.1.
4A.03	643	645	01	Delete "(a) Pedestrians lawfully within an associated crosswalk, and (b) Other vehicles lawfully within the intersection" from the second sentence of A.1 and insert "other vehicles and to pedestrians and bicyclists lawfully within the intersection or an adjacent crosswalk at the time the signal is exhibited."
4A.03	643	645	01	Delete the last sentence of A.1
4A.03	643	645	01	In the first sentence of A.2, replace "displayed" with "shown", replace "is permitted to" with "may", replace "such" with "the", delete "such", delete "as is", and replace "displayed" with "shown."

Part	Original Page Number	Final Page Number	Paragraph Number	Change
4A.03	643	645	01	Delete the second sentence of A.2 and replace with "The vehicular traffic shall yield the right-of-way to pedestrians and bicyclists lawfully within an adjacent crosswalk and to other traffic lawfully using the intersection."
4A.03	643	645	01	Replace "CIRCULAR GREEN" with "green", replace "are permitted to" with "may", replace "any" with "a", and delete "associated" in the first sentence of A.3.
4A.03	643	645	01	Delete the second sentence of A.3
4A.03	643	645	01	Delete A.4
4A.03	644	645	01	Replace "CIRCULAR YELLOW" with "yellow" in the first sentence of B.1.
4A.03	644	645	01	After "signal indication" in B.1, delete "is thereby warned that the related green movement or the related flashing arrow movement is being terminated or that a steady red signal indication will be displayed immediately thereafter when vehicular traffic shall not enter the intersection. The rules set forth concerning vehicular operation under the movement(s) being terminated shall continue to apply while the steady CIRCULAR YELLOW signal indication is displayed" and insert "shall stop before entering the nearest crosswalk at the intersection or at a limit line when marked, but if the stop cannot be made in safety, a vehicle may be driven cautiously through the intersection."
4A.03	644	645	01	Replace all text in B.2. with "A YELLOW ARROW indication has the same meaning as a CIRCULAR YELLOW indication, except that it applies only to vehicle operators intending to make the movement indicated by the arrow."
4A.03	644	645	01	Replace "shall not start to cross the roadway" with "are advised that there is insufficient time to cross the roadway and a pedestrian then starting to cross shall yield the right of way to all vehicles." in B.3.
4A.03	644	646	01	Replace "CIRCULAR RED" with "red" in the first sentence of C.1.
4A.03	644	646	01	Replace "shall stop at a clearly marked stop line; but if there is no stop line, traffic shall stop before entering the crosswalk on the near side of the intersection; or if there is no crosswalk, then before entering the intersection; and shall remain stopped until a signal indication to proceed is displayed, or as provided below" with "shall stop before entering the crosswalk on the near side of the intersection or at a limit line when marked or, if there is no crosswalk or limit line, before entering the intersection and shall remain standing until a green indication is shown except as provided below" in the first sentence of C.1.

Part	Original Page Number	Final Page Number	Paragraph Number	Change
4A.03	644	646	01	Replace the second and third sentences of C.1. with "Vehicular traffic facing a steady red signal, after stopping before entering the crosswalk on the near side of the intersection or at a limit line when marked or, if there is no crosswalk or limit line, before entering the intersection, may make a right turn from a 1-way or 2-way street into a 2-way street or into a 1-way street carrying traffic in the direction of the right turn or may make a left turn from a 1-way or 2-way street into a 1-way roadway carrying traffic in the direction of the left turn, unless prohibited by sign, signal, marking, light, or other traffic control device. The vehicular traffic shall yield the right of way to pedestrians and bicyclists lawfully within an adjacent crosswalk and to other traffic lawfully using the intersection."
4A.03	644	646	01	Replace all text in C.2. with "A RED ARROW indication has the same meaning as a CIRCULAR RED indication, except that it applies only to vehicle operators intending to make the movement indicated by the arrow."
4A.03	644	646	01	Replace "roadway" with "highway unless they can do so safely and without interfering with vehicular traffic" in C.3.
4A.04	644	646	00	Insert new Support paragraph 00: "Section 257.614(1) of the "Michigan Vehicle Code" provides meanings to flashing traffic signal indications for vehicular traffic. Paragraph 01 of this Section has been modified to reflect the "Michigan Vehicle Code."
4A.04	644	646	01	Delete "and pedestrians" from the first sentence of A.1.
4A.04	644	646	01	Replace text in B.1. with "When a yellow lens is illuminated with rapid intermittent flashes, drivers of vehicles may proceed through the intersection or past the signal only with caution."
4A.04	644	646	01	Replace all text in B.2. with "A YELLOW ARROW indication has the same meaning as a CIRCULAR YELLOW indication, except that it applies only to vehicle operators intending to make the movement indicated by the arrow."
4A.04	645	646	01	Delete B.3 and B.4.
4A.04	645	646	01	Replace all text in C.1 with "When a red lens is illuminated by rapid intermittent flashes, drivers of vehicles shall stop before entering the nearest crosswalk at an intersection or at a limit line when marked and the right to proceed shall be subject to the rules applicable after making a stop at a stop sign."

Part	Original Page Number	Final Page Number	Paragraph Number	Change
4A.04	645	646	01	Replace all text in C.2. with "A RED ARROW indication has the same meaning as a CIRCULAR RED indication, except that it applies only to vehicle operators intending to make the movement indicated by the arrow."
4A.04	645	646	01	Delete C.3 and C.4.
4A.05	646	646	00	Insert new Support paragraph 00: "The "Michigan Vehicle Code" does not provide meanings for bicycle symbol signal indications for bicyclists. The "Uniform Vehicle Code" is the primary source for the standards for the meanings of separate bicycle signal face indications as provided in this Section."
4A.06	646	647	00	Insert new Support paragraph 00: "Section 257.613(2) of the "Michigan Vehicle Code" provides meanings to pedestrian signal indications. Paragraph 01 of this Section has been modified to reflect the "Michigan Vehicle Code.""
4A.06	646	647	01	Replace "shall be permitted to start to cross the roadway in the direction of the signal indication, possibly in conflict with turning vehicles. Pedestrians shall yield the right-of-way to vehicles lawfully within the intersection at the time that the WALKING PERSON (symbolizing WALK) signal indication is first shown" with "may proceed across the highway in the direction of the signal and shall be given the right of way by the drivers of all vehicles" in Item B.
4A.06	646	647	01	Insert "steady or" before "flashing" in Item C.
4A.06	646	647	01	Replace "roadway in the direction of the signal indication. Any pedestrian who has already started to cross the roadway on a steady WALKING PERSON (symbolizing WALK) signal indication shall continue to proceed to the far side of the traveled way of the street or highway, unless otherwise directed by a traffic control device to proceed only to the median of a divided highway or only to some other island or pedestrian refuge area (see Section 3C.12)" with "highway in the direction of the signals, but a pedestrian who has partially completed crossing on the walk interval of the signal shall proceed to a sidewalk or safety island while the don't walk interval of the signal is showing" in Item C.
4A.06	646	647	01	Delete Item D.
4B.03	650	651	02	Insert "while taking care not to create new sight line restrictions" at end of Item H.
4C.01	651	652	12	After "justified", insert "(see Paragraph 20 of this Section for the primary consideration in the engineering study to determine if the signal is justified)."
4C.01	652	653	13	Insert after "median" the following text: ", even if the median width is greater than 30 feet,"

Part	Original Page Number	Final Page Number	Paragraph Number	Change
4C.02	653	654	02	Table 4C-1: Insert the following title above the 2nd table: "Condition B - Interruption of Continuous Traffic"
4D.05	668	669	01	Insert at end of Item A: "A minimum of one signal face shall be located over the travel portion of the roadway (MCL 257.612(1))."
4D.06	670	671	04	Delete paragraph and insert "Paragraph 04 deleted."
4D.06	670	671	05A	Insert new Guidance paragraph 05A: "Where signal face obstructions occur, engineering judgment should determine the treatment to be implemented."
4F.01	682	683	03A	Insert new Support paragraph 03A: "Items B.4 and F.5 in Paragraph 03 of this Section provide requirements for avoiding or mitigating the yellow trap situation. The yellow trap situation occurs in cases where a permissive left-turn movement exists on an approach via a steady CIRCULAR YELLOW or YELLOW ARROW signal indication after the termination of a CIRCULAR GREEN indication while opposing through-traffic continues to be shown a CIRCULAR GREEN indication. This can give the false impression to left-turning drivers that the opposing through traffic also has a steady yellow indication. Avoidance of the yellow trap situation is preferable to mitigation of it through utilization of the ONCOMING TRAFFIC MAY HAVE EXTENDED GREEN (W25-2) sign (see Section 2C.44)."
4F.02	684	686	13A	Insert new Support paragraph 13A: "In Michigan, it is typical to utilize Protected Only Mode left turn phasing for approaches that have more than one left turn lane and opposing traffic."
4F.06	689	690	03	Insert new Option paragraph 03: "A LEFT sign may be mounted above a vertically-arranged signal face."
4F.08	692	694	08	Insert new Option paragraph 08: "A LEFT sign may be mounted above a vertically-arranged signal face."
4F.19	710	712	07	Delete "(see Section 11-106 of the "Uniform Vehicle Code")"
4F.19	710	712	07A	Insert new Support paragraph 07A: "The color white is used as the distinctive indication in Michigan."
4P.02	745	747	05	Insert at end of paragraph: "A minimum of one signal face shall be located over the travel portion of the roadway (MCL 257.612(1))."
4P.02	745	747	09	Delete "Option:" and paragraph. Insert "Paragraph 09 deleted."
4P.02	745	747	10	Delete paragraph and insert "Paragraph 10 deleted."

2025 MMUTCD Changes to the 11th Federal Edition
December 2025

PART: Part 5

CHANGES:

Part	Original Page Number	Final Page Number	Paragraph Number	Change
5A.03	760	762	02	Add Support paragraph: "Section 257.2b of the "Michigan Vehicle Code" provides additional definitions associated with automated vehicle technologies."
5B.01	762	764	03	Insert "Michigan" before "Standard Highway Signs" in Item C.
5B.02	762	764	02	Add "s" after "system".

2025 MMUTCD Changes to the 11th Federal Edition
December 2025

PART: Part 6

CHANGES:

Part	Original Page Number	Final Page Number	Paragraph Number	Change
6B.01	770	772	20A	Insert new Support paragraph 20A: "MCL 257.627(6) within the "Michigan Vehicle Code" establishes speed limits when entering and passing through a work zone."
6B.02	770	772	02	Delete text in Paragraph 02 and insert: "Michigan State Statute has the following provision for defining a work zone and "temporary traffic control device." Insert MCL 257.79d.
6B.05	771	774	01A	Insert new Guidance paragraph 01A: Neither work activity nor storage of equipment, vehicles, or material should occur within a transition area."
6B.09	776	779	04	Insert new Support paragraph 04: "MCL 247.291 and MCL 247.292 provide for the closing of highways or bridges for construction, the erecting of barriers, and the providing of detours."
6C.04	781	785	04	Delete item D for Lighting.
6C.04	782	785	04	Change "E" to "D" since "D" was deleted.
6D.01	783	786	00	Insert new Support paragraph 00: "In Michigan, the term "Traffic Regulator" is often used in place of the term "Flagger." For purposes of this Manual, the two terms are considered to be synonymous (see Section 1C.02).
6D.05	785	788	00	Insert new Support paragraph 00: "Additional information and a detailed outline of the traffic regulator procedures and conduct is contained in the Michigan Department of Transportation "Traffic Regulators Instruction Manual.""
6D.06	786	789	06	Insert new Support paragraph 06: "MIOSHA General Rule R408.40133 provides requirements for illuminating a jobsite where work is being performed."
6F.01	789	792	09	Add "Michigan" before "Standard Highway Signs"
6F.02	790	793	N/A	Figure 6F-1. Revise the distances on the pictured signs to "AHEAD".
6F.03	792	795	N/A	Figure 6F-2. Replace "W20-7" sign with "W20-7b".
6G.02	793	796	01	Add "Michigan" before "Standard Highway Signs"

Part	Original Page Number	Final Page Number	Paragraph Number	Change
6G.08	797	800	06	Insert new Support paragraph 06: "MCL 257.601b of the "Michigan Vehicle Code" prescribes fines for moving violations in work zones."
6G.08	797	800	07	Insert new Support paragraph 07: "MCL 257.627c(1)(a) of the "Michigan Vehicle Code" prescribes signing requirements when an automated speed enforcement system is utilized in a work zone."
6H.01	798	802	02	Add "Michigan" before "Standard Highway Signs"
6H.02	801	805	N/A	In Figure 6H-1 on Sheet 3 of 4, add Traffic Regulator (W20-7b) sign. Add "Michigan" before "Standard Highway Signs" in all instances in figure note. Replace distances shown on signs with "AHEAD" - seven instances.
6H.04	804	808	N/A	In Table 6H-1, add "(MI) Traffic Regulator (symbol)".
6H.12	806	810	01	Change reference from "Figure 6H-1" to "Figure 6I-1" to reflect the correct reference.
6H.13	806	810	01	Change reference from "Figure 6H-1" to "Figure 6I-1" to reflect the correct reference.
6H.15	806	810	N/A	Change title to "Flagger (Traffic Regulator) Signs (W20-7, W20-7a, and W20-7b)"
6H.15	806	810	01A	Add Option "01A The Traffic Regulator (W20-7b) sign (see Figure 6H-1) may be used in lieu of the Flagger (W20-7) sign if the flagger is utilizing a STOP/SLOW paddle as the hand-signaling device (see Section 6D.02)."
6H.15	806	810	02	Add "or Traffic Regulator" after "Flagger".
6H.38	810	814	03	Add "Michigan" before "Standard Highway Signs".
6I.01	811	816	07	Insert "Standard:" before Paragraph 07 and update font type for Paragraph 07 to bold to indicate it as a standard.
6I.02	811	816	N/A	Table 6I-1. Add "Arrow" to sign name for sign M4-10.
6J.03	814	819	03	Delete "a group of at least three retroreflective markers equally spaced at no greater than 5 feet shall be installed every 40 feet" and insert "they shall be placed according to Paragraph 5 of Section 3B.17."
6J.03	814	819	04	Delete "the markers shall be equally spaced at no greater than 10 feet, with retroreflective or internally illuminated units at a spacing no greater than 20 feet" and insert "they shall be placed according to Paragraph 6 of Section 3B.17."

Part	Original Page Number	Final Page Number	Paragraph Number	Change
6K.01	815	820	04A	Insert new Support paragraph 04A: "In Michigan, the typical spacing between cones, tubular markers, vertical panels, drums, and barricades is 50 feet when used for taper channelization and 100 feet when used for tangent channelization where the speed limit is greater than 45 mph. When the speed limit is 45 mph or less, the recommended spacings in paragraph 4 of this Section are utilized."
6L.04	829	834	N/A	Figure 6L-2: Delete "XX FT" on W20-1 and W20-4 signs and insert "AHEAD". Replace W20-7 sign with a W20-7b.
6L.06	834	839	N/A	Figure 6L-3: For Item 3., delete the 4 corners Flashing Caution image and text.
6M.02	837	842	06	Insert new Support paragraph 06: "MCL 247.291a(1a) within the "Michigan Vehicle Code" provides criteria for requiring the utilization of temporary concrete barriers on freeways."
6M.08	840	845	05	Delete text and insert: "MIOSHA General Rule R408.40133 provides requirements for illuminating a jobsite where work is being performed."
6N.01	842	847	19A	Insert new Support paragraph 19A: "MCL 257.698(5) within the "Michigan Vehicle Code" provides for the allowable use of flashing, oscillating, or rotating lights in Michigan."
6N.04	843	849	06	Delete "- and" in the first sentence.
6N.18	852	856	07	Delete text and insert: "MIOSHA General Rule R408.40133 provides requirements for illuminating a jobsite where work is being performed."
6N.18	852	856	08	Insert new Support paragraph 08: "MCL 247.291a within the "Michigan Vehicle Code" provides criteria for the utilization of temporary traffic barriers during night-time lane and total closures on freeways."
6N.19	852	857	05	Insert "Support:" prior to paragraph 05.
6N.19	853	858	N/A	Figure 6N-1. Delete "XX MILE" on W20-1 and W20-5 signs and insert "AHEAD".
6N.19	853	858	N/A	Figure 6N-1. Change R9-4a to R4-9a.
6O.01	854	859	02	Insert at end of paragraph: "Michigan statute uses the term "emergency scene", and its definition is located in MCL 257.601b(5) within the "Michigan Vehicle Code.""
6P.01	865	870	N/A	Figure 6P-3. Replace ROAD WORK NEXT XX MILES (G20-1) signs with ROAD WORK AHEAD (W20-1) signs.
6P.01	867	872	N/A	Figure 6P-4. Replace arrow board showing 4 corners with arrow board showing a bar.
6P.01	869	874	N/A	Figure 6P-5. Insert "or appropriate end treatment" after "Crash cushion". Add "(Optional)" for W7-3aP plaque. Add "(Optional)" for W16-2P plaque.

Part	Original Page Number	Final Page Number	Paragraph Number	Change
6P.01	873	878	N/A	Figure 6P-7. Delete "XX FT" on first W20-1 sign and insert "AHEAD". Delete second W20-1 sign. Replace "Appiication" with "Application".
6P.01	874	879	N/A	Notes for Figure 6P-8. Insert Item 2 under Guidance: "Cardinal direction plaques should be used with route signs." Delete Item 5. Renumber remaining items accordingly.
6P.01	875	880	N/A	Figure 6P-8. Revise all M1-5 route signs to the Michigan design. Add M3-4 cardinal direction plaques to each detour assembly. Delete "1500 FT" on W20-2 sign and insert "AHEAD". Delete "500 FT" and "1000 FT" on W20-3 signs and insert "AHEAD".
6P.01	876	881	N/A	Notes for Figure 6P-9. Insert Item 4 under Guidance: "Cardinal direction plaques should be used with route signs." Delete Item 6. Renumber remaining items accordingly.
6P.01	877	882	N/A	Figure 6P-9. Revise all M1-5 route signs to the Michigan design.
6P.01	879	884	N/A	Figure 6P-10. Delete "XX FT" on W20-1 signs and insert "AHEAD". Delete "XX FT" on W20-4 signs and insert "AHEAD." Insert "(optional)" after "W16-2P". Change W20-7 signs to W20-7b.
6P.01	885	890	N/A	Figure 6P.13. Change W20-7 signs to W20-7b.
6P.01	886	891	N/A	Notes for Figure 6P-14. Delete Item 1 and insert "Haul road crossings should be illuminated where existing light is inadequate."
6P.01	887	892	N/A	Figure 6P-14. Delete "(optional)" beneath "Temporary marking" labels. Change W20-7 sign to W20-7b.
6P.01	891	896	N/A	Figure 6P-16. Change W20-7 signs to W20-7b.
6P.01	893	898	N/A	Figure 6P-17. Replace arrow board showing 4 corners with arrow board showing a bar.
6P.01	899	904	N/A	Figure 6P-20. Remove top set of R3-1/R3-2 signs since road is open to local traffic. Replace R3-2 with a Main St SOUTH DETOUR Up Arrow sign. Move the M4-9R (modified) sign in the top right quadrant of the upper right intersection to be on the far side of the intersection since it is a pull thru. Add a M4-9R (modified) sign for Main St NORTH as a pull thru sign to the top left quadrant of the lower right intersection.
6P.01	903	908	N/A	Figure 6P-22. Remove "(optional)" from first arrow board and add it to second arrow board. Add additional drums to better delineate the right turn opening.
6P.01	905	910	N/A	Figure 6P-23. Insert arrow board showing merge right arrow at end of taper within closed lane, in front of the R3-7L sign. Add additional drums to better delineate the left turn lane.
6P.01	907	912	N/A	Figure 6P-24. Delete "(optional)" from first arrow board. Add additional drums to better delineate the right turn opening.

Part	Original Page Number	Final Page Number	Paragraph Number	Change
6P.01	909	914	N/A	Figure 6P-25. Delete "(optional)" from arrow board.
6P.01	913	918	N/A	Figure 6P-27. Change W20-7 signs to W20-7b.
6P.01	918	923	N/A	Notes for Figure 6P-30. Delete "XX FT" in Item 1 and insert "AHEAD".
6P.01	920	925	N/A	Notes for Figure 6P-31. Delete "XX FT" in Item 3 and insert "AHEAD".
6P.01	921	926	N/A	Figure 6P-31. Delete "(optional)" from arrow board.
6P.01	923	928	N/A	Figure 6P-32. Delete second W20-5L sign. Delete second W20-5R sign. Delete "XX FT" on first W20-5L sign and insert "AHEAD". Delete "XX FT" on first W20-5R sign and insert "AHEAD".
6P.01	925	930	N/A	Figure 6P-33. Delete "XX FT" on W20-1 and W20-5R signs and insert "AHEAD".
6P.01	927	932	N/A	Figure 6P-34. Insert "or appropriate end treatment" after "Crash cushion".
6P.01	933	938	N/A	Figure 6P-37. Replace "1 MILE" with "AHEAD" on the W20-1 sign. Replace "1/2 MILE" with "AHEAD" on the W20-5aR sign.
6P.01	935	940	N/A	Figure 6P-38. Delete "XX FT" on W20-1 and W20-5L signs and insert "AHEAD".
6P.01	937	942	N/A	Figure 6P-39. Delete "XX FT" on W20-1 and W20-5R signs and insert "AHEAD". Delete second W20-5R sign.
6P.01	941	946	N/A	Figure 6P-41. Change the white-on-green E5-1 sign to be black-on-orange.
6P.01	943	948	N/A	Figure 6P-42. Delete "XX MILE" on W20-1 and W20-5R signs and insert "AHEAD". Change the white-on-green E5-1 signs to be black-on-orange.
6P.01	945	950	N/A	Figure 6P-43. Delete "XX FT" on W20-1 sign and insert "AHEAD".
6P.01	947	952	N/A	Figure 6P-44. Delete "XX MILE" on W20-1 and W20-5R signs and insert "AHEAD".
6P.01	951	956	N/A	Figure 6P-46. Delete "XX FT" on W20-1 and W20-4 signs and insert "AHEAD". Change W20-7 signs to W20-7b.
6P.01	963	968	N/A	Figure 6P-52. Delete "XX FT" from W20-4 signs and insert "AHEAD." Change W20-7 signs to W20-7b.
6P.01	965	970	N/A	Figure 6P-53. Change W20-7 sign to W20-7b.

2025 MMUTCD Changes to the 11th Federal Edition
December 2025

PART: Part 7

CHANGES:

Part	Original Page Number	Final Page Number	Paragraph Number	Change
7A.02	970	974	09A	Insert new Standard: "School crossings shall be established in accordance with Section 257.613a of the "Michigan Vehicle Code."
7B.01	971	975	N/A	Table 7B-1: Insert "End Double Fines Zone" as new sign R2-11a. Delete "Where Children are Present" S4-2P plaque.
7B.01	972	976	10	Change "Standard Highway Signs" to "Michigan Standard Highway Signs" .
7B.02	972	976	01	Change "traffic" to "moving".
7B.02	972	976	04	Delete "or local".
7B.02	972	976	04A	Insert new Support: "Michigan State Statute has the following provisions on school zones." Insert MCL 257.627a excerpt.
7B.02	972	977	05	Delete "Zone". The S1-1 sign name is School per Table 7B-1.
7B.02	972	977	06	Delete "Zone". The S1-1 sign name is School per Table 7B-1.
7B.02	973	977	N/A	Figure 7B-1 (Sheet 1 of 2). Delete S4-2P plaque. Insert R2-11a "End Double Fines Zone" sign. Delete "Zone" from S1-1 sign title. Change "20" to "25" on R2-1, S5-1, S4-5, and S4-5a signs.
7B.02	974	978	N/A	Figure 7B-1 (Sheet 2 of 2). Change "STATE" TO "LOCAL" on R1-6 series signs and R1-9c sign. Delete Note 1. Change "2." to "1." and change "3." to "2.".
7B.02	975	979	N/A	Figure 7B-2: Insert R2-6aP FINES DOUBLE signs below the S1-1 sign/S4-3P plaque combinations in the figure. Change "20" to "25" on applicable R2-1 signs.
7B.03	976	980	00	Insert new Support: "Michigan State Statute has the following provisions for establishing school crossings." Insert 257.613a.
7B.03	976	981	12	Insert "in accordance with the provisions of Section 2B.20" after "may be used". Delete "The STATE LAW legend on the R1-6 series signs may be omitted."
7B.03	976	981	14	Insert "in accordance with the provisions of Section 2B.20" after "may be used". Delete "The STATE LAW legend on the R1-9 series signs may be omitted."

Part	Original Page Number	Final Page Number	Paragraph Number	Change
7B.04	978	983	03	Insert new Support: "Michigan State Statute has the following provisions for receiving and discharging pupils with buses." Insert 257.1855.
7B.05	978	984	01	Replace "based upon an engineering study or where a reduced school speed limit is specified for such areas by statute." with "in accordance with Section 257.627a of the "Michigan Vehicle Code."
7B.06	979	985	N/A	Figure 7B-4: Change "20" to "25" on R2-1 signs.
7B.06	980	986	01	Change "traffic" to "moving".
7B.06	980	986	02	Change "traffic" to "moving" and insert "as defined in Section 257.601b of the "Michigan Vehicle Code" to the end of the first sentence.
7B.06	980	986	02	Item B, insert "END DOUBLE FINES ZONES (R2-11a) sign (See Figure 7B-1),"
7B.06	980	986	03	Change "traffic" to "moving".
7B.06	980	987	06	Delete "B. A WHEN CHILDREN ARE PRESENT (S4-2P) plaque (see Figure 7B-1), or". Change "C." to "B."
7B.06	981	987	N/A	Figure 7B-5: Change "traffic" to "moving" in title - on both sheets.
7B.06	981	987	N/A	Figure 7B-5: Insert R2-11a END DOUBLE FINES ZONE sign with S5-2 and R2-11 options on Sheet 1 of 2 and Sheet 2 of 2.
7B.06	983	989	07	Change "traffic" to "moving".
7D.01	985	991	03A	Insert new Support: "Information for the organization, operation, and administration of an adult crossing guard program is given in the "Michigan Adult School Crossing Guard Manual.""
7D.01	985	991	03B	Insert new Support: "Sections 257.613b, 257.613c, and 257.613d of the "Michigan Vehicle Code" define the responsibilities of an adult crossing guard."

2025 MMUTCD Changes to the 11th Federal Edition
December 2025

PART: Part 8

CHANGES:

Part	Original Page Number	Final Page Number	Paragraph Number	Change
8B.02	996	1003	N/A	Figure 8B-1: Insert "STOP ON RED SIGNAL (R10-6b) sign.
8D.01	1017	1024	N/A	Figure 8D-1: Add "STOP ON RED SIGNAL" sign to figure.
8E.06	1040	1047	N/A	Figure 8E-6: Delete "optional" from swing gate label.
8E.07	1041	1048	N/A	Figure 8E-7: Add "STOP ON RED SIGNAL" sign to figure.
8E.09	1043	1050	N/A	Figure 8E-8: Add "STOP ON RED SIGNAL" sign to figure.
8E.09	1044	1051	N/A	Figure 8E-9: For Drawing A, revise the fence lines located between the road and the sidewalk in the upper right and lower left to be exit gates that extend across the road.
8E.09	1044	1051	N/A	Figure 8E-10: Add "STOP ON RED SIGNAL" sign to figure.
8E.09	1045	1052	N/A	Figure 8E-11: Add "STOP ON RED SIGNAL" sign to figure.
8E.09	1046	1053	N/A	Figure 8E-12: Add "STOP ON RED SIGNAL" sign to figure.

2025 MMUTCD Changes to the 11th Federal Edition
December 2025

PART: Part 9

CHANGES:

Part	Original Page Number	Final Page Number	Paragraph Number	Change
9B.17	1059	1067	01A	Insert new Support paragraph: "Figure 9B-4 is deleted in accordance with Paragraph 00 of this Section."
9B.17	1060	1068	N/A	Remove Figure 9B-4 and insert: "Figure 9B-4 deleted".

2025 MMUTCD Changes to the 11th Federal Edition
December 2025

PART: Appendix

CHANGES:

Part	Original Page Number	Final Page Number	Paragraph Number	Change
Appendices	N/A	N/A	N/A	No changes.