REPORT OF TEST ON DAILY ASPHALT CEMENT ORIGINAL

FI	ΙF	303
	ᄂᄂ	202

SECTION I.	D. NO.	JOB NO.		LAB N	Ю.			DATE REPORTED	
	_		MA	TERIAL					
		200-250	2	50-300					
Γ	AC-10	AC-5	□ A	C-2.5	🗌 AC-1				
	7								
				EVELING		NG	SHOULL	DER CURB	
	900	□ 1100	□ 1300	□ 1500	□ 1800	□ 2B	□ 2C	□ 3B	
PERCENT			0/						
		0	RIGINAL A	SPHALT CE	EMENT				
PLED				DATE REC	EIVED				
TEST RESULTS					SPECIFICATION				
PENETRATION				(4.00.19.a-1 & 8.04.03a)					
100g, 5 s	ec. dmm	FAIL	ED						
(Absolute)									
Poises		FAIL	ED						
REMARKS									
		GRADE AC-10 USE TOP O. 700 900 4B 4C PERCENT PERCENT PERCENT PERCENT CON 100g, 5 sec. dmm (Absolute)	ON GRADE	ON GRADE	MATERIAL ON GRADE	MATERIAL ON GRADE 120-150 200-250 250-300 GRADE AC-10 AC-5 AC-2.5 AC-1 USE AC-10 AC-5 AC-2.5 AC-1 USE TOP BINDER LEVELING WEARI O. 700 900 1100 1300 1500 1800 AB 4C 11A 13 13A 36A PERCENT	MATERIAL ON GRADE 120-150 200-250 250-300 GRADE AC-10 AC-5 AC-25 AC-1 USE TOP BINDER LEVELING WEARING O 100 1300 1500 1800 2B 4B 4C 11A 13 13A 36A 36B PERCENT	MATERIAL ON GRADE 120-150 200-250 250-300 GRADE AC-10 AC-5 AC-2.5 AC-1 USE TOP BINDER LEVELING WEARING SHOULD 0. 1700 900 1100 1300 1500 1800 2B 2C 4B 4C 11A 13 13A 36A 36B OTI PERCENT % ORIGINAL ASPHALT CEMENT CITY PLED DATE RECEIVED (A100.19.a-1 & 8.04.03a) 100g, 5 sec. dmm FAILED	

Michigan Department of Transportation 528A (5/00)