

CPM-HMA OVERLAY & COLDMILL AND HMA OVERLAY (DETAILED INSPECTION)

Field Evaluation of Warranty Performance

FOR USE WITH 12SP-501 (R,S) and 20SP-501 (P,Q)

CONTRACTOR	INSPECTION DATE
CONTROL SECTION	INSPECTED BY
JOB NUMBER	REVIEWED BY (Optional)
ROUTE	RESIDENT ENGINEER
INSPECTION LIMITS	

LONGITUDINAL CRACKING/OPEN JOINT (THRESHOLD LIMIT - 132 FEET)

SEGMENT NUMBER	LANE DESCRIPTION	DISTANCE FROM POB TO START OF SEGMENT (miles)	TOTAL LENGTH OF DISTRESS (ft)	COMMENTS
LC-1				
LC-2				
LC-3				
LC-4				
LC-5				
LC-6				
LC-7				
LC-8				
LC-9				
LC-10				
LC-11				
LC-12				
LC-13				
LC-14				
LC-15				
LC-16				
LC-17				
LC-18				
LC-19				
LC-20				
LC-21				
LC-22				
LC-23				
LC-24				
LC-25				
LC-26				
LC-27				
LC-28				
LC-29				
LC-30				

DISTRIBUTION WHEN WARRANTY WORK IS REQUIRED: REGION OFFICE, TSC MANAGER, RESIDENT ENGINEER, WARRANTY CONTRACTOR, SURETY COMPANY.