

**CPM-HMA OVERLAY & COLDMILL AND HMA OVERLAY
(DETAILED INSPECTION)**

Field Evaluation of Warranty Performance

FOR USE WITH 12SP-501 (R,S) and 20SP-501 (P,Q)

CONTRACTOR	INSPECTION DATE
CONTROL SECTION	INSPECTED BY
JOB NUMBER	REVIEWED BY (Optional)
ROUTE	RESIDENT ENGINEER
INSPECTION LIMITS	

DEBONDING

(THRESHOLD LIMIT - 132 FEET)

SEGMENT NUMBER	LANE DESCRIPTION	DISTANCE FROM POB TO START OF SEGMENT (miles)	TOTAL LENGTH OF DISTRESS (ft)	COMMENTS
D-1				
D-2				
D-3				
D-4				
D-5				
D-6				
D-7				
D-8				
D-9				
D-10				
D-11				
D-12				
D-13				
D-14				
D-15				
D-16				
D-17				
D-18				
D-19				
D-20				
D-21				
D-22				
D-23				
D-24				
D-25				
D-26				
D-27				
D-28				
D-29				
D-30				

DISTRIBUTION WHEN WARRANTY WORK IS REQUIRED: REGION OFFICE, TSC MANAGER, RESIDENT ENGINEER, WARRANTY CONTRACTOR, SURETY COMPANY.