Michigan Department of Transportation 1193C (08/2023)

INSPECTION LIMITS

CPM-HMA OVERLAY & COLDMILL AND HMA OVERLAY

(DETAILED INSPECTION)

Field Evaluation of Warranty Performance

File 107

	FOR USE WITH 125P-50T (R,S) and 205P-50T (P,Q)
CONTRACTOR	INSPECTION DATE
CONTROL SECTION	INSPECTED BY
JOB NUMBER	REVIEWED BY (Optional)
ROUTE	RESIDENT ENGINEER

RAVELING	(THRESHOLD LIMIT - 105.6 FEET)				
SEGMENT NUMBER	LANE DESCRIPTION	DISTANCE FROM POB TO START OF SEGMENT (miles)	TOTAL LENGTH OF DISTRESS (ft)	COMMENTS	
RV-1					
RV-2					
RV-3					
RV-4					
RV-5					
RV-6					
RV-7					
RV-8					
RV-9					
RV-10					
RV-11					
RV-12					
RV-13					
RV-14					
RV-15					
RV-16					
RV-17					
RV-18					
RV-19					
RV-20					
RV-21					
RV-22					
RV-23					
RV-24					
RV-25					
RV-26					
RV-27					
RV-28					
RV-29					
RV-30					