

CPM-HMA OVERLAY & COLDMILL AND HMA OVERLAY (DETAILED INSPECTION)

Field Evaluation of Warranty Performance

FOR USE WITH 12SP-501 (R,S) and 20SP-501 (P,Q)

CONTRACTOR	INSPECTION DATE
CONTROL SECTION	INSPECTED BY
JOB NUMBER	REVIEWED BY (Optional)
ROUTE	RESIDENT ENGINEER
INSPECTION LIMITS	

FLUSHING (THRESHOLD LIMIT - 26.4 FEET)

SEGMENT NUMBER	LANE DESCRIPTION	DISTANCE FROM POB TO START OF SEGMENT (miles)	TOTAL LENGTH OF DISTRESS (ft)	COMMENTS
FL-1				
FL-2				
FL-3				
FL-4				
FL-5				
FL-6				
FL-7				
FL-8				
FL-9				
FL-10				
FL-11				
FL-12				
FL-13				
FL-14				
FL-15				
FL-16				
FL-17				
FL-18				
FL-19				
FL-20				
FL-21				
FL-22				
FL-23				
FL-24				
FL-25				
FL-26				
FL-27				
FL-28				
FL-29				
FL-30				

DISTRIBUTION WHEN WARRANTY WORK IS REQUIRED: REGION OFFICE, TSC MANAGER, RESIDENT ENGINEER, WARRANTY CONTRACTOR, SURETY COMPANY.