Michigan Department Of Transportation 1978 (09/11)

## PROPOSED RIDE QUALITY EXCLUDED AREAS

CONTROL SECTION	JOB NUMBER		ROUTE			LANE				
Submit one form for each lane with ride quality.										
Proposed Excluded Feature (eg intersection, bridge)	Location Descript (eg 0.3 miles south o Road)		Station		Distance from Ride P.O.B. (feet)	Mileage from Ride P.O.B. (miles)		Exclusion Approved by MDOT? (P=Predetermi ned)		Distance Correction for Station Equations
Ride POB (1)		st	tart		0	0	0.00			
		St	tart				Г			
			nd				— ☐ yes	☐ no		
			tart				-	yes yes	no	
			nd				L			
			tart						☐ no	
			nd				L			
			tart					ges no		
			nd				L		∐ no	
			tart					☐ yes ☐ no		
			nd				L			
			start				_			
			nd					yes	☐ no	
			start end				-	☐ yes ☐ no		
			tart				г	_		
			end start end					☐ yes ☐ no		
							-	yes no		
-			tart				-			-
			end					yes 🗌 no		
Ride POE (2)			nd							
Notes:  (1) Ride Point of Beginning (POB) will be 20 feet after the start of new pavement surface, unless otherwise agreed upon.  (2) Ride Point of Ending (POE) will be 20 feet before the end of the new pavement surface, unless otherwise agreed upon.  (3) Distance and Mileage from Ride POB must be adjusted for any station equations within the job.										
CONTRACTOR SIGNATURE AND DATE		MDOT APPROVAL AND DATE					PAGE OF			