

UTILITIES - PERMITS SECTION
REAL ESTATE DIVISION



PERMIT NO. _____
TRUNKLINE _____
NAME OF PERMIT _____
APPLICANT _____

PERMIT ATTACHMENT FOR
COMMERCIAL DRIVEWAY
UNCURBED TRUNKLINE


08-17-98
PLAN DATE

PA-08

SHEET
01 OF 02

NOTES

1. PLACE ____ LFT OF ____ INCH CULVERT ____ FEET FROM CENTERLINE OF PAVEMENT WITH END SECTION AT EACH END.
GRATES SHOULD BE USED ON END SECTIONS FOR CULVERTS 18" AND LARGER WHICH ARE LESS THAN 30' FROM THE PAVEMENT. HEADWALLS SHALL NOT BE USED FOR DRIVEWAY CULVERTS.
2. THE SURFACE SHALL BE EQUAL TO OR BETTER THAN THE FOLLOWING:
 - a. ____ INCH BITUMINUS MIXTURE ____ TOP
 ____ INCH BITUMINUS MIXTURE ____ LEVELING
 ____ INCH BITUMINUS MIXTURE ____ BASE
 ____ INCH COMPACTED GRAVEL OR CRUSHED STONE
 ____ INCH SUBBASE COMPATIBLE WITH THAT USED ON THE HIGHWAY
 - b. ____ OF REINFORCED CONCRETE ON ____ INCH OF COMPACTED GRAVEL OR CRUSHED STONE AND ____ SUBBASE COMPATIBLE WITH THAT USED ON THE HIGHWAY.
 - c. CONCRETE GRADE P1 SHALL BE USED
3. ALL WORK WITHIN THE RIGHT OF WAY SHALL BE DONE IN ACCORDANCE WITH CURRENT MICHIGAN DEPARTMENT OF TRANSPORTATION STANDARD SPECIFICATIONS FOR CONSTRUCTION AND ACCORDING TO THE ADMINISTRATIVE RULES OF ACT 200, P.A. OF 1969.
4. SLOPE DRIVEWAY APPROACH AWAY FROM PAVEMENT AT 1/2" /FT FOR 12 FEET.
5. DISTURBED AREAS SHALL BE RESTORED WITH TOPSOIL AND SEED OR SOD ONLY. MINIMUM OF 3 INCHES OF TOPSOIL REQUIRED.
6. A DRIVEWAY SHALL BE CONSTRUCTED SO THAT IT DOES NOT ADVERSELY AFFECT THE HIGHWAY DRAINAGE. THE DRAINAGE AND THE STABILITY OF THE HIGHWAY SUBGRADE SHALL NOT BE ALTERED BY DRIVEWAY CONSTRUCTION OR ROADSIDE DEVELOPMENT.
7. CURB IS TO EXTEND TO ROW LINE OR A MINIMUM OF 10' BEYOND THE RADIUS OR AS DIRECTED BY THE ENGINEER.

UTILITIES - PERMITS SECTION REAL ESTATE DIVISION 	PERMIT NO. _____ TRUNKLINE _____	PERMIT ATTACHMENT FOR COMMERCIAL DRIVEWAY UNCURBED TRUNKLINE		
	NAME OF PERMIT _____ APPLICANT _____	08-05-98 PLAN DATE	PA-08	SHEET 02 OF 02